Nothing holds you back



Conver is a Dutch manufacturer that develops and builds cutting-edge machines. We have built a reputation for quality and reliability for over 30 years. Conver machines enable you perform water management responsibly. We rely on our knowledge and experience to provide custom solutions for floating, amphibious and on-land machines. At Conver, we know exactly what our customers need: professional advice and great service. That makes Conver your brand of choice for water management.

Experience the C86 silt pusher



IT'S IN OUR NATURE

Conver C86 silt pusher

The C86 silt pusher was designed to be efficient, durable and easy to use. This compact silt pusher is ideal for maintaining and cleaning ponds and watercourses. The durable design of the C86 enables it to restore the bottom profile while removing sludge at the same time.

Built on experience

The C86 silt pusher is the result of many years of experience and innovation. This is immediately evident in the ergonomic and user-friendly design that enables you to do your maintenance work efficiently.

Nothing holds you back

The C86 is equipped with a double hydraulic winch. This proved drive system gives the silt pusher major pulling power both forward and in reverse, even in shallow water and under the heaviest conditions. This means the silt pusher is virtually unaffected by coarse debris and obstructions.



Push blades

A variety of push blades are available for the C86. They can easily be switched. You can choose blades with a maximum working depth up to 2 metres and a working width up to over 8 metres.

Custom work

Of course a number of implements are available for this machine, making it even more versatile. A number of options are also available for the operator to personalise the workplace.



Contact

For more information contact our office at +31 183 447272 or send an e-mail to sales@conver.com.

SPECIFICATIONS CONVER C86	
Dimensions (LxWxH)*	8,00 x 1,76 x 1,42 m
Weight	3.300 kg (Excluding implements)
Depth	approx. 0,45 m
Colour	Orange RAL2004/Grey RAL7012
Engine	Water-cooled 4 cylinder, 36 kW at 3000 rpm
Fuel consumption	5 – 6 L/hour
Front winch**	5,000 kg, 12 mm 6×36 WSC 240 m, 12 m/min
Rear winch**	2,500 kg, 10 mm 6×36 WSC 260 m, 24 m/min
Controls	Electrical operation
Hydraulic system	1 x Load Sensing plunger pump, 1 x Gear pump
Fuel tank	75 L
Hydraulic tank	90 L with intake and return filter





^{**} Hydraulic winches with automatic spooling system



^{*} Operation without push blade